

Peristaltic Chemical Feed Pumps Since 1957

Simplicity Makes The Difference

Mechanical Pump

Classic Series




single head
fixed output



single head
adjustable output



double head
fixed output



double head
adjustable output

- Output range at 25 psi/1.7 bar:
0.2-170 gpd, 0.8-644 lpd
0.02-15 oz/min, 0.56-447 ml/min
- Output range at 100 psi/6.9 bar:
0.2-40 gpd, 0.8-151 lpd
0.02-3.6 oz/min, 0.56-105 ml/min
- 3 snap-fit subassemblies allow quick serviceability without tools
- Patented mechanical control adjustable from 5-100%
- Change pump capacity by replacing tube size and/or gears
- Self-priming, won't lose prime, automatic degassing
- Pump tube lubrication not required
- Will not clog from minor debris
- Able to run dry without damage

Tank System

STS Series



Ships preassembled for convenience
and easy installation

- 15 gallon: 25 1/4" h x 20 1/2" OD
30 gallon: 37 1/2" h x 20 1/2" OD
- Gray (UV resistant) or natural (translucent)
- Rugged polyethylene construction for indoor or outdoor applications
- Compact and lightweight design minimizes space requirements
- Vertical 45 or 85 pump mount with containment basin
- Locking, child-resistant lid
- Solution level indicators
- Includes rain roof and spill recovery set-up
- Tanks also sold separately



3174 DeSalvo Road
Jacksonville, Florida 32246
Phone 904-641-1666
US Toll Free 800-683-2378
Fax 904-642-1012

www.stenner.com
sales@stenner.com
Hours of Operation (EST)
Mon – Thu. 7AM – 5PM
Friday 7AM – Noon

© G. H. Stenner & Co., Inc
All Rights Reserved



Variable Speed

SVP Series



Optional 4-20mA input

- Max. output at 25 psi/1.7 bar:
85 gpd, 322 lpd, 8 oz/min, 223 ml/min
- Max. output at 100 psi/6.9 bar:
40 gpd, 151 lpd, 3.6 oz/min, 105 ml/min
- Adjustable control 5-100% in 1% increments,
20:1 turndown ratio, non scalable
- 120 or 220VAC/60Hz and 230 or 250VAC/50Hz (Intl)
- 4-button keypad with up/down arrows, prime button,
and on/off switch
- 4-character LED display
- Polycarbonate corrosion-resistant housing
- Self-priming, won't lose prime, automatic degassing
- Change pump capacity by replacing tube size
- Will not clog from minor debris
- Able to run dry without damage

Programmable Pump

BDF Series



Easy to program 24-hour or
7-day event timer

- Output at 25 psi/1.7 bar: 0.06-21 oz per event
- Output at 100 psi/6.9 bar: 0.06-4.5 oz per event
- 120VAC/60Hz
- Customize dosages with using simple switches
- Programmable up to 24 events per day
- Battery supplied for back-up of programmed event times
- Manual priming switch
- Self-priming, won't lose prime, automatic degassing
- Pump tube lubrication not required
- Will not clog from minor debris
- Able to run dry without damage

Pump Control Module

PCM Series



Hays® water meter also sold separately

- Used with a 45 or 85 fixed output pump and a
Hays® dry contact water meter
- Delivers precise chemical feed proportional to the system's
flow rate
- 3 models: 1-second, 5-second, and 10-second adjustable
on-time durations
- Packaged system available and includes:
meter, fixed rate pump, and PCM
- Microcontroller with triac output
- Interchangeable time range settings
- 8 amp relay output
- Immediate reset time
- Minimal signal duration 10 milliseconds
- ABS plastic housing
- 10' power cord & heavy-duty jacketed signal input cable