


MODEL	DIMENSIONS (INCHES)							INLET/ OUTLET SIZE	BRINE CONN. SIZE*	DRAIN CONN. SIZE
	A	B	C	D	E	F	G			
HW4650-1	32	29	7	18	30	18	18	3/4" MNPT	3/8"	1/2" MNPT
HW4650-1D	32	29	7	18	30	18	42	3/4" MNPT	3/8"	1/2" MNPT
HW4650-2	43	30	8	18	30	18	18	3/4" MNPT	3/8"	1/2" MNPT
HW4650-2D	43	30	8	18	30	18	44	3/4" MNPT	3/8"	1/2" MNPT
HW4650-3	48	31	9	24	30	24	24	3/4" MNPT	3/8"	1/2" MNPT
HW4650-3D	48	31	9	18	30	18	46	3/4" MNPT	3/8"	1/2" MNPT
HW4650-4	48	32	10	18	30	18	18	3/4" MNPT	3/8"	1/2" MNPT
HW4650-4D	48	32	10	18	30	18	48	3/4" MNPT	3/8"	1/2" MNPT
HW4650-5	55	32	10	18	30	18	18	3/4" MNPT	3/8"	1/2" MNPT
HW4650-5D	55	32	10	18	30	18	48	3/4" MNPT	3/8"	1/2" MNPT

* BRINE CONNECTION IS A COMPRESSION FITTING

NOTES:

- (1) ALL PIPING & VALVES TO BE FURNISHED BY OTHERS.
- (2) AN ELECTRICAL OUTLET SHOULD BE PROVIDED WITHIN 5 FEET OF THE EQUIPMENT
- (3) UNIONS SHOULD BE LOCATED ON THE INLET AND OUTLET CONNECTIONS OF CONTROL VALVE TO FACILITATE SERVICING.
- (4) DO NOT MAKE A DIRECT CONNECTION TO THE DRAIN. PROVIDE AN AIR GAP OF AT LEAST FOUR TIMES THE DIAMETER OF THE DRAIN PIPE TO CONFORM TO THE SANITATION CODES AND TO PERMIT THE OBSERVATION OF DRAIN FLOW.
- (5) ALLOW 24 INCHES ABOVE THE SOFTENER FOR FILLING.



PO BOX 1059
 MEDIA, PA 19063
 TELEPHONE: 610.358.0717
 FAX: 610.358.4642
 E-MAIL: sales@reskem.com
 INTERNET: http://www.reskem.com

This document is the property of RES-KEM CORP. and thereby subject to confidential use. It shall not be reproduced, furnished to others or used for other than its intended purpose without the express written consent of RES-KEM CORP.

HOT WATER SERIES
 WATER
 SOFTENER

